



akdeio[®]
forest products ground materials
import export
marketing industry and trade
LIMITED COMPANY



LINOVİL

Excellent
Quality
for Perfect
Floors



akdeio

Forest Products Ground Materials Import Export Marketing Industry and Trade
LIMITED COMPANY

Mobile Company: +90 532 250 65 29

Phone: +90 212 111 11 11

Address: Atakent Mah. 243. Sk. No:6 Tema İstanbul Sitesi 7/B No:1 Halkalı / K.Çekmece İstanbul / TÜRKİYE



akdeio[®]
forest products ground materials
import export
marketing industry and trade
LIMITED COMPANY

www.akdeio.com.tr
info@akdeio.com.tr

[akdeio](#)
[akdeioorman](#)

beranet
Nispetiye Tesisleri Kat: 5/11



Who We Are?

Established in 2013, Tasarım Yapı Kimyasalları San. Tic. Ltd. Şti. manufactures under the brand name Linovil in its state of the art modern facilities in Istanbul. With our sectoral experience of more than 25 years, the importance we attach to quality, people, the environment and the satisfaction of our customers; we continue on our way by growing in Turkey and international markets.

We provide service with our wide product range consisting of nearly 50 varieties in the Lamination, Carpet, Construction and Flooring sectors.

Sustainable production at high quality standards, providing the most reliable services before and after sales form the basis of our long-standing customer relations.

In this direction, we provide pre-sales and after-sales services to our customers in Turkey and in various countries of the world with our R&D laboratories, experienced marketing and technical service teams.

Tasarım Yapı Kimyasalları
San. Tic. Ltd. Şti.

Our Products



LİNOVİL CC 548

PVC Flooring Adhesive



Areas of Usage:

Linovil CC 548 is used for bonding PVC coating materials and textile floor coverings with PVC, PU and latex backing.

Ground Preparation:

The floor must be dry, clean, crack-free and resistant to pressure. Selflevelling recommendation screeds should be used for uneven surfaces.

Application:

Before using the product, it should be mixed well and spread on the floor with a toothed comb. After 10-30 minutes, the flooring material is glued to the base. Ambient temperature during application should be +15°C. The tools used and the stains that will occur can be monitored through water conduction.

Technical Informations:

- Consumption: 350gr/m² with B1, 300gr/m² with A3 trowel
- Waiting Time: 10-30 minutes
- Storage: 12 months under normal conditions +5°C

Product Code	Package	Pallet Capacity	Consumption	Color
CC 548	20 kg bucket	40	300-350 gr/m ²	Grey - White

LİNOVİL OS 1010

Carpet Tile Adhesive



Areas of Usage:

Linovil OS-1010 Carpet tile adhesive is a dispersion-based adhesive that maintains its bonding properties. It is used for bonding PVC, wool, felt, backed carpet tiles and free PVC tiles.

Application:

The surfaces to be bonded must be free of dust, dirt, oil and all kinds of factors that will reduce the bonding. Linovil OS-1010 adhesive is applied with a foam roller. Depending on the weather conditions, the application can be made after waiting for 10-30 minutes for the adhesive to dry.

Technical Informations:

- Color: White
- Density: 1.05 g/cm³
- Working Time: 24 Hours
- Waiting Time: 45 Minutes
- Consumption: (with roll) 50-150 gr/m²
- Shelf Life: 12 Months

Suitable for underfloor heating systems.

Product Code	Package	Pallet Capacity	Consumption	Color
OS 1010	10 kg drum	60	50-150 gr/m ²	White

LİNOVİL POWER 502

PVC Wall Coating Adhesive



Areas of Usage:

It is used for bonding all kinds of PVC wall covering, bonding rubber up to 2.5 mm thickness and PVC PUR backed textile covering.

Application:

The surface must be clean, dry, free of cracks and sound. Remove dust, oil and dirt. Surface defects should be corrected. Do not apply when the surface temperature is below 15 °C and the humidity is above 75%. During the application, the material should be mixed thoroughly and applied to the surface with the help of suitable toothed comb. Tools and stains can be cleaned with water.

Technical Informations:

- Color : White
- Density : 1,2 kg/lit
- Waiting Time : 10-30 minutes
- Resistance to Mechanical Effects : After 24 Hours
- Last Dry : After 72 Hours
- A2 Trowel : 280 gr/m²
- A3 Trowel : 300 gr/m²

Product Code	Package	Pallet Capacity	Consumption	Color
Power 502	14 kg bucket	50	280-300 gr/m ²	White

LİNOVİL LN 550

Linoleum Adhesive



Areas of Usage:

It is used for natural floor coatings of the genus Linoleum, floor and wall coverings of the genus of cork.

Application:

The product should be mixed well before use and spread on the floor with toothed comb. After 10-30 minutes, the flooring material is adhered to the base. Ambient temperature should be + 15°C during application. Tools and stains can be cleaned with water.

Technical Informations:

- Color : Beyaz
- Density : 1,2 kg/lit
- Waiting Time : 5-15 minutes
- Resistance to Mechanical Effects : After 24 Hours
- Last Drying : After 72 Hours
- Consumption m² : 400-450 gr/m² With A2 Adhesive Trowel
- Storage : 12 Months under normal condutions above +5°C

Product Code	Package	Pallet Capacity	Consumption	Color
LN 550	20 kg bucket	40	400-450 gr/m ²	White

LİNOVİL ESD 505

Conductive PVC Flooring Adhesive



Definition:

ESD-505 is a special dispersion based, conductive adhesive containing organic and inorganic substances. ESD-505 is a solvent-free acrylic-based water-based adhesive. It is used for bonding conductive PVC LVT and carpet floor coverings to the floor.

For Conductor Applications:

The copper strip is adhered to the bottom of each coating roll, depending on the type of product. These strips must be connected to each other and grounded.

Technical Informations:

- Appearance: Cream liquid
- Viscosity: Low
- Consumption: 300 - 350 g/m²
- Waiting Time: 15-45 minutes
- Mechanical Effects Dur.: 24 hours
- Grounding Resistance: <math> < 3 \times 10^5 </math> ohm according to EN 13415
- Packaging: 20 kg plastic bucket

Product Code	Package	Pallet Capacity	Consumption	Color
ESD 505	20 kg bucket	40	300-350 gr/m ²	Cream

LİNOVİL OS 300

Universal Primer



Areas of Usage:

It is a dispersion primer used on absorbent and non-absorbent floors and walls, which can be applied indoors and outdoors. It is used to increase the adhesion before screed and to prevent dusting. For mineral leveling screeds. It is applied on the dry concrete floor, on the leveling screed.

Application:

Sufficient amount of product is poured into a container and applied with the help of a roller or brush.

Technical Informations:

- Penetrates into the subfloor
- Binds dust on the floor
- Reduces the absorbency of the floor
- For indoors
- Solvent Free

Product Code	Package	Pallet Capacity	Consumption	Color
OS 300	10 kg drum	60	100-150 gr/m ²	Light Blue

LİNOVİL OS 310

Universal Primer



Areas of Usage:

It is a dispersion primer used on absorbent and non-absorbent floors and walls, which can be applied indoors and outdoors. It is used to increase the address before screed and to prevent dusting. For mineral leveling screeds. It is applied on the dry concrete floor, on the leveling screed.

Application:

Sufficient amount of product is poured into a container and applied with the help of a roller or brush.

Technical Informations:

- Penetrates into the subfloor
- Binds dust on the floor
- Reduces the absorbency of the floor
- For indoors
- Solvent Free

Product Code	Package	Pallet Capacity	Consumption	Color
OS 310	10 kg drum	60	100-150 gr/m ²	White

LİNOVİL TS 10

Baseboard and Carpet Adhesive



Areas of Usage:

It is used for bonding PVC skirting and wooden skirtings, rubber floor coverings, textile-based jute-based carpets.

Application:

The surfaces to be bonded must be free of dust, dirt, oil and all kinds of factors that will reduce the bonding. The adhesive is applied to both surfaces with a brush. After waiting for 10-30 minutes for the adhesive to dry according to the weather conditions, the parts to be bonded are pressed and adhered to each other.

Storage:

Shelf Life is 1 year from the date of production under suitable storage conditions. The lids of the packages should be closed immediately after the application and consumed on time. Please store between 10°C-30°C. Protect the product against freezing and store below 10°C.

Product Code	Package	Pallet Capacity	Consumption	Color
TS 10	17 lt tin	40	200-250 gr/m ²	Yellow

Baumit Nivello Quattro

Self Levelling Screed



Areas of Usage:

It can be used in all buildings, indoors. It is suitable for cement, concrete, calcium sulfate and asphalt floors. It can be used on floors subject to light loads, in places not exposed to heavy traffic, especially in places where pedestrian or wheeled office vehicles are used. It is applied for surface leveling before ceramic, granite, marble, parquet, laminate, carpet and PVC coating floors.

Surface Preparation:

The substrate must be clean, dry, dust-free, sound, not frozen, salt/lime vomited. There should be no loose parts on it. Cement, plaster, plaster etc. on the floor. If there are substances, the floor should be cleaned. In applications to be made on concrete and existing screed, priming the surface is important to increase adhesion.

Application Conditions:

Recommended working ambient temperature is between +5°C and +35°C. It should not be applied in high humidity or very hot weather and especially under direct sunlight.

Product Code	Package	Pallet Capacity	Consumption	Color
Nivello Quattro	25 kg sack	60	1,50-1,70 kg/m ²	White

Baumit E 160

Floor Screed



Areas of Usage:

It can be used in all buildings, indoors and outdoors. Thanks to its homogeneous mixture, this factory-mixed product offers the same and high quality at every point of application, compared to screeds prepared with the classical method. The product, which can be used as floating screed, movable screed or joint screed, is suitable for underfloor heating systems. It is suitable for laying on after 2-4 weeks. The alum product stands out with its very low "back moisture" feature.

Surface Preparation:

The substrate must be clean, dry, dust-free, sound, not frozen, salt/lime vomited. There should be no loose parts on it. Cement, plaster, plaster etc. on the floor. If there are substances, the floor should be cleaned. In applications to be made on concrete and existing screed, priming the surface is important to increase adhesion.

Application Conditions:

Recommended working ambient temperature is between +5°C and +35°C. It should not be applied in high humidity or very hot weather and especially under direct sunlight.

Product Code	Package	Pallet Capacity	Consumption	Color
E 160	40 kg sack	40	20 kg/m ²	Grey





akdelo

Forest Products Ground Materials Import Export Marketing Industry and Trade
LIMITED COMPANY

Mobile: +90 532 500 51 52 Mobile Company: +90 532 250 65 29

Phone: +90 212 111 11 11

Address: Atakent Mah. 243. Sk. No:6 Tema İstanbul Sitesi 7/B No:1 Halkalı / K.çekmece İstanbul / TÜRKİYE

Address: Khelvachauri, Akhalshehis Meurneoba Mah. 3-CU Sk. No: 26 Batumi / GEORGIA

Akdelo Orman Ürünleri Zemin Malzemeleri İthalat İhracat Pazarlama San. ve Tic. LTD. ŞTİ.



www.akdelo.com.tr

info@akdelo.com.tr

onder@akdelo.com.tr

[akdelo](https://www.facebook.com/akdelo)

[akdeloorman](https://www.instagram.com/akdeloorman)